

M354 Series

8" True Flat Display

Your Stylish & Compact Choice



Features and Benefits

- / Support P-Cap Touch
- / USB or VGA Interface Available
- / Optional Die-Casting Aluminum Base
- / Easy for Installation - One USB Cable Needed
- / Best Choice for Space Limited Retail / Hospitality Settings
- / Spill Proof and Anti-Dust

M Series Small Size Touch/Non Touch Monitor



USB Interface Available



VGA Interface Available



75x75mm VESA Wall Mount



Optional Die-Casting Stand

Specification

Model Name	M354ND	M354NC	M354RD / PD	M354RC / PC
Display Size	8"			
Optimal Resolution	800 x 600			
Panel Brightness	350 cd/m ² (typ)			
Contrast Ratio	500 : 1 (typ)			
Respond Time	25 ms (typ)			
Viewing Angle (L/R/U/D)	70 / 70 / 50 / 70			
Tilt Angle	N/A			
Input Video Signal	DIN	USB B Type	DIN	USB B Type
Touch	Non Touch		Resistive Touch (RD/RC) Capacitive Touch (PD/PC)	
Power Consumption	6W	2.5W	6W	2.5W
Input Frequency	Horizontal: 31.5~60.2 kHz ; Vertical: 56.3~75 Hz			
Power Supply	DC 12V +/- 10%	DC 5V +/- 10%	DC 12V +/- 10%	DC 5V +/- 10%
Temperature	Operating: 0°C~40°C (32F~102F) ; Storage: -10°C~50°C (14F~122F)			
Humidity	Operating: 20%~80% ; Storage: 10%~90%			
Weight	0.7 Kgs (1.78 lbs)		0.8 Kgs (1.76 lbs)	
Physical Dimension (W x H x D)	202 x 163 x 34.5 (mm) 79.6 x 64.2 x 13.6 (inch)			
Optional	White, Wall Mount Kit, Stand			

* The right has been reserved to change the specification without prior notice

Contact

<http://www.poindus.com>

Poindus Systems Corp. Headquarters (TW)

5F, No.59, Ln. 77, Xing-Ai Rd., Neihu Dist.,
Taipei City 114, Taiwan. R.O.C

☎ + 886 27721 4688

☎ + 886 27721 2289

✉ sales@poindus.com

UK

12 Chancerygate Business Centre, Whiteleaf Road,
Hemel Hempstead HP3 9HD

☎ + 44 330 555 0081

☎ + 44 330 555 0082

✉ puk@poindus.com